



TPLO Crescentic Saw Blade

veterinary technology for life
Eickemeyer®

Precise, low-vibration vision control with minimal bone loss

TPLO Crescentic Saw Blade


The TPLO saw blades have specially shaped recesses in the cutting blade with a slightly wider, stepped cutting edge compared to the entire blade and thus reduce the heat transfer generated by friction to the bone.

The triangular shaft of the sawblades is compatible with most motor systems.

The sawblades with 0,6 mm blade thickness are available in radiuses of 12, 15, 18, 21, 24, 27 and 30 mm.



192907



- ▶ Minimal heating due to recesses in the cutting surface
- ▶ Reduced vibration
- ▶ Good visibility through hole perforation
- ▶ Standard triangular shaft

- ▶ Radius: 12 mm
- ▶ Length: 45 mm

192907

- ▶ Radius: 15 mm
- ▶ Length: 45 mm

192908

- ▶ Radius: 18 mm
- ▶ Length: 45 mm

192909

- ▶ Radius: 21 mm
- ▶ Length: 45 mm

192912

- ▶ Radius: 24 mm
- ▶ Length: 45 mm

192910

- ▶ Radius: 27 mm
- ▶ Length: 50 mm

192913

- ▶ Radius: 30 mm
- ▶ Length: 50 mm

192911

EICKEMEYER®

3 Windmill Business Village
Brooklands Close, Sunbury-on-Thames
Surrey, TW16 7DY, United Kingdom

T 020 8891 2007
F 020 8891 2686
E info@eickemeyer.co.uk

TELEPHONE 020 8891 2007

www.eickemeyer.co.uk